# IMPLEMENTATION OF COASTAL R&D INNOVATIONS IN HURRICANE SUPPLEMENTAL PROJECTS

### **USACE GALVESTON DISTRICT**

Shubhra Misra, PhD, PE Hydraulic Engineer

"The views, opinions and findings contained in this report are those of the authors(s) and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other official documentation."





### **Acknowledgements**

- USACE SWG Sabine-to-Galveston and Coastal TX team members (Cris Michalsky, Eddie Irigoyen, Brad Burrows, Jacob Breaux, Molly Ross, Jason Caldwell, Himangshu Das and many others)
- USACE SWG Leadership (Coraggio Maglio, Joe King, Rob Thomas, Edmond Russo)
- USACE ERDC (Chris Massey, Jeff Melby, Norberto Nadal, Victor Gonzales, Matt Malej, Jeff King, Todd Bridges and many others)
- USACE SWF and USACE LRC (Helena Mosser, Matt Dircksen)
- USACE HQ (Kate White)
- Various Academic Faculty (Thomas Wahl, Clint Dawson, Jim Kirby, Fengyan Shi, Pat Lynett, Billy Edge, Jens Figlus, and many others)
- S2G Local Sponsors (Drainage District 7, Velasco Drainage District, Orange Country Drainage District)

### **Biography**


- BS Ocean Engineering and Naval Architecture (India 1997)
- MS and PhD Coastal Engineering/Civil and Environmental Engineering (U. of Delaware – 2005)
- HPA-Halcrow-CH2MHill-Jacobs Senior Coastal Engineer (New York City; 2005 – 2009)
- Ben C. Gerwick-COWI Project Manager (Houston; 2009 2011)
- Professional Engineer, Civil (Water Resources), TX (2010)
- AECOM Senior Project Manager/Principal Coastal Engineer (Houston; 2011 – 2012)
- Chevron SME/Marine Facilities Engineer (Houston; 2012 2018)
- USACE SWG Hydraulic Engineer/S2G HH-Coastal Lead (Galveston; 2018 – Present)








## SWG Supplemental Projects





## SWG Supplemental Projects

### • Sabine-to-Galveston (S2G): PED













## Coastal Storm Surge and Wave Hazards Modeling and Analysis

#### ERDC CHL














Figure 8: USACE's "new" Probabilistic Coastal Hazard Analysis (StormSim-PCHA) (Nadal-Caraballo et al. 2018)

### Relative Sea Level Change and Mean Sea Level


#### **USACE Sea Level Change Curve Calculator (2017.55)**





## Results: RSLC After 50-Year Service Age (Start of Service Life : 2027)









## Phase-resolving Boussinesq Models (Coastal Wave Hazards)

University of Southern California; ERDC CHL; University of Delaware












## Phase-resolving Boussinesq Models (Infragravity Waves)

 Texas A&M University, Galveston; University of Delaware; University of Southern California; ERDC CHL






Infragravity waves (0.003 – 0.05 Hz) dominated the water motion onshore of the berm crest over 24-hours proximate to storm landfall resulting in a peak water surface elevation (WSE) of 1.7 m in the backshore.




## Phase-resolving Boussinesq Models (Ship-induced Waves and Sediment Transport)

• ERDC CHL; University of Delaware; Lamar University; University of Houston




## **Ship-induced Scour and Empirical Assessment**

#### SWG









THRUSTER-INDUCED SCOUR					
Input Name and Description	Unit	Input Valu			
P_thruster (Installed power of thruster)	W				
D_thruster (Thruster diameter)	m				
L (Distance between outflow and quay wall)	m				
D85	m				
h_w (thruster tip clearance to seabed)	m				

PROPELLER-INDUCED SCOUR					
Input Name and Description	Units	Input Value			
P_prop (Installed power)	W	1454115			
D_prop (Propeller diameter)	m	2.18			
C3 (Ducted or free propeller:					
1.17 for ducted prop or 1.43 for free prop)	-	free			
Single or twin prop?	-	twin			
D85	m	0.005			
h_w (propeller tip clearance to seabed)	m	5.04			
f_p (% of engine power used:					
0.1 if maneuvering, 1.0 if fully operational)	-	1			

	Thruster		Pr	ор	
RESULTS	German	Dutch	1	German	Dutch
Scour Depth (m)	#DIV/0!	#DIV/0		2.32	2.32


CLEAR THRUSTER INPUTS


Samson

LEAR PROPELLE	R INPUTS		
		J	

## **Compound Flooding**


 University of Central Florida (Data and Statistical Analysis); University of Texas, Austin (Two-way ADCIRC and HEC-RAS coupling); SWG-MVN-SAJ Workshop






## Engineering-with-Nature (EwN) / Natural and Nature-Based Features (NNBF)

• ERDC, DRC (Various Universities), Texas A&M, Galveston











## **Challenges and Opportunities**

- Significant (implementable) advancements have been made, but equally significant challenges remain
  with regard to uncertainty and accuracy, as well as fundamental understanding of physical processes, in
  implementing presently available tools and methodologies
- Coastal storm hazard models both for surge and waves must be comprehensively validated against observational data from historical storms, updated incorporating latest topographic/bathymetric data, and continually validated for new events/data.
- Integrate phase-resolving wave models (e.g. Boussinesq) to supplement/complement spectral phase-averaged wave models (e.g. STWAVE, SWAN) into coastal storm hazards modeling and analysis
- Develop process-based and calibrated/validated models to supplement empirical tools (with large uncertainties, and limited parameter range validity) presently being used (e.g. ship-induced waves; runup and overtopping)
- Develop quantitative understanding of the importance of Compound Flooding (specifically, interaction of coastal surge and inland rainfall-induced runoff) and reliable, accurate and validated (translatable) tools and best practice/guidance that can be applied on projects
- Quantify performance metrics, including geomorphic evolution of NNBF with EwN principles and develop best practice/design guidance